SOYSOLV® AR PRO

Biodegradable Asphalt Solvent

TECHNICAL DATA SHEET

DESCRIPTION

SoySolv AR Pro is a high-performance bio-based asphalt and tar remover, specifically formulated from renewable resources to replace diesel and citrus solvents. AR Pro is formulated with a proprietary surfactant package designed to penetrate, emulsify, and pull dissolved asphalt off surfaces.

Through extensive research and field testing, SoySolv AR Pro is proven to be more efficient and safer than diesel or citrus based solvents for dissolving asphalt.

KEY BENEFITS

- Economical Pricing – Lower cost than d-limonene based products
- Advanced cleaning power – removes the toughest build-up
- Slow Evaporation Rate – Leaves behind slick film preventing future build-up
- 100% Biodegradable
- Water Rinseable – proprietary surfactants
- Safe and easy to use, non-toxic formulation
- Lab and field tested to outperform diesel and last longer than citrus

USAGE DIRECTIONS

- DO NOT DILUTE
- ***REMOVE ASPHALT BUILD-UP:***
  1.) Liberally coat build-up on tools or equipment
  2.) Allow 5-20 minutes for SoySolv AR Pro to penetrate build-up
  3.) Remove build-up with pressure washer or scraping tool

  For thick build-up, allow for longer dwell time. SoySolv AR Pro has a very low evaporation rate – the longer it sits the better it works.

TECHNICAL DATA

APPEARANCE	Red
WEIGHT	7.4 lbs. per gallon
FLASH POINT	> 200 ° F
SHELF LIFE	12 months properly stored
GHS HAZARDS	See Safety Data Sheet
ECOTOXICITY	100% Biodegradable
FREEZE POINT	> 30°F
WATER SOLUBILITY	Emulsifiable
ODOR	Floral

PRECAUTIONS

- Wear protective gloves/protective clothing/eye protection. Use PPE as required per Safety Data Sheet
- Read and understand the Safety Data Sheet before each use
- Product should be stored above 40° F and below 120° F. Protect from freezing. Store in tightly sealed, full containers
- Warning: to help prevent damage to painted surfaces, wipe off and/or rinse with water
- Product may expand during storage causing pressure to build-up. Open container carefully
- If spilled on fresh pavement, flush with water immediately
- **Additional precautions, safety information and first aid are contained in the SDS**

www.soysolv.com 877-769-7658 Po Box 470233 Cleveland, Ohio 44147 USA

Technical Data Sheet Disclaimer:

The information provided in this document is believed to be accurate and is offered in good faith; however, no warranty, express or implied, is made regarding its accuracy, completeness, or suitability for any particular purpose. All technical data, including physical and chemical properties, are presented as typical values and are not guaranteed specifications. Variations may occur due to raw material differences, production variability, or testing conditions.

It is the responsibility of the user to determine the suitability of the product for their specific application and to ensure compliance with all applicable laws, regulations, and safety standards. SoySolv Biosolvents, LLC disclaims all warranties, including but not limited to implied warranties of merchantability, fitness for a particular purpose, and non-infringement of intellectual property rights. Nothing herein shall be construed as granting a license under any patent or other intellectual property right.

No liability is assumed for any direct, indirect, incidental, or consequential damages resulting from the use, handling, storage, or reliance on this information or the product described. Product specifications are subject to change without notice. Users should consult the most recent Safety Data Sheet (SDS) prior to use.