SOYSOLV® AR

Biodegradable Asphalt Solvent

TECHNICAL DATA SHEET

DESCRIPTION

SoySolv AR is a highly effective bio-based asphalt solvent and release agent, specifically formulated from renewable resources to replace diesel and citrus solvents. Through extensive research and field testing, SoySolv AR is proven to be more efficient and much safer than diesel fuel or citrus based solvents for dissolving asphalt and preventing asphalt adhesion. SoySolv AR's high flash point makes it a safe and highly effective drag slat cleaner that prevents asphalt build up and lubricates drag slat equipment.

KEY BENEFITS

- Economical Pricing – Half the cost of d-limonene products
- Slow Evaporation Rate – Leaves behind slick film preventing future buildup
- High Flash Point
- Environmentally safe solvent - 100% Biodegradable
- Safe and easy to use, non-toxic formulation
- Lab and field tested to outperform diesel and last longer than citrus

USAGE DIRECTIONS

- DO NOT DILUTE
- ***REMOVE ASPHALT BUILD-UP:***
  1.) Liberally coat build-up on tools or equipment
  2.) Allow 10-20 minutes for SoySolv AR to penetrate build-up
  3.) Remove build-up with pressure washer or scraping tool

  For thick build-up, allow for longer dwell time. SoySolv AR has a very low evaporation rate – the longer it sits the better it works.

- ***PREVENT ASPHALT ADHESION:***
  1.) Liberally coat tools or equipment where build-up occurs
  2.) Re-apply when asphalt starts to stick

  SoySolv AR will form a molecular barrier and last for multiple applications before re-application is required

TECHNICAL DATA

APPEARANCE	Clear to Amber
WEIGHT	7.3 lbs. per gallon
FLASH POINT	> 200° F
SHELF LIFE	12 months properly stored
GHS HAZARDS	None
ECOTOXICITY	100% Biodegradable
FREEZE POINT	35 F
WATER SOLUBILITY	None
ODOR	Mild, fatty
US DOT	Ships as non-regulated

PRECAUTIONS

- Wear protective gloves/protective clothing/eye protection. Use PPE as required
- Read and understand the Safety Data Sheet before each use
- Product should be stored above 40° F. Protect from freezing
- Warning: to help prevent damage to painted surfaces, wipe off and/or rinse with water
- If spilled on fresh pavement, flush with water immediately
- **Additional precautions, safety information and first aid are contained in the SDS**

www.soysolv.com 877-769-7658 Po Box 470233 Cleveland, Ohio 44147 USA

Technical Data Sheet Disclaimer:

The information provided in this document is believed to be accurate and is offered in good faith; however, no warranty, express or implied, is made regarding its accuracy, completeness, or suitability for any particular purpose. All technical data, including physical and chemical properties, are presented as typical values and are not guaranteed specifications. Variations may occur due to raw material differences, production variability, or testing conditions.

It is the responsibility of the user to determine the suitability of the product for their specific application and to ensure compliance with all applicable laws, regulations, and safety standards. SoySolv Biosolvents, LLC disclaims all warranties, including but not limited to implied warranties of merchantability, fitness for a particular purpose, and non-infringement of intellectual property rights. Nothing herein shall be construed as granting a license under any patent or other intellectual property right.

No liability is assumed for any direct, indirect, incidental, or consequential damages resulting from the use, handling, storage, or reliance on this information or the product described. Product specifications are subject to change without notice. Users should consult the most recent Safety Data Sheet (SDS) prior to use.